



CORROSION RESISTANT

LED LIGHTING SERIES





The Corrosion Resistant Series from Vision X consists of the 10-Watt, 50-Watt, 140-Watt, and 280-Watt LED lighting fixtures. Each fixture is designed to withstand high-risk environments where aluminum housings are susceptible to rapid deterioration due to chemicals exposed from processing plants.

All products are subjects to rigorous product testing to ensure long term durability.

Plastic Tri-Coated Aluminum

Polycarbonate Lens

50,000 Hrs Life Span

UL1598a Rated for Wet Locations

- IP68/69K Rated
- **UL** Certified
- - 5 Year Warranty
- ✓ For Acid Mist Environments

50-WATT JUNCTION BOX All-In-One LED Light

140-WATT AC LIGHT



PROTECTIVE TRI-COATING

The secondary yellow plastic coating on the maintenance and long term illumination.



EASY INSTALLATION

Making any electrical replacements a breeze, the quick connect cable allows for a simple and speedy lighting install.





280-WATT AC LIGHT



TECHNICAL:

Lumens:	1,000 lm
Wattage:	10W
Operating Voltage:	90-264V AC 127-370V DC
Operating Temp:	-40°C ~ 60°C
Amp Draw:	0.09A@115V AC 0.04A @ 230V AC 0.04 @ 277V AC
Beam Pattern:	180° Ultra Wide Flood with Frosted or Clear Lens
Fixture Weight:	2 lbs.

ITEM#: LSYSM40180F (180° Optics)



TECHNICAL:

Lumens:	7,000 lm
Wattage:	50W
Operating Voltage:	90-305V AC 127-431V DC
Operating Temp:	-40°C ~ 60°C
Amp Draw:	0.43A@115V AC 0.22A @ 230V AC 0.18 @ 277V AC
Beam Pattern:	180° Ultra Wide Flood
Fixture Weight:	8 lbs.

ITEM#: **LSY0225180QC** (180° Optics) ITEM#: **LSY033060QC** (60° Optics) ITEM#: **LSY033090QC** (90° Optics)



TECHNICAL:

Lumens:	21,000 lm
Wattage:	140W
Operating Voltage:	90 - 305VAC 127 - 431VDC 180-528VAC High Voltage Available
Operating Temp:	-40°C ~ 60°C
Amp Draw:	1.22A @ 115VAC 0.61A @ 230VAC 0.51A @ 277VAC
Beam Pattern:	60° 90°
Fixture Weight:	24 lbs.

ITEM#: LSY063060STRQC (60° Optics) ITEM#: LSY063090STRQC (90° Optics)



TECHNICAL:

Lumens:	36,000 lm
Wattage:	280W
Operating Voltage:	90 - 305VAC 127 - 431VDC 180-528VAC High Voltage Available
Operating Temp:	-40°C ~ 60°C
Amp Draw:	2.43A @115VAC 1.22A @ 230V AC 1.01A @ 277VAC
Beam Pattern:	60° 90°
Fixture Weight:	37.05 lbs.

ITEM#: LSY066060STRQC (60° Optics) ITEM#: LSY066090STRQC (90° Optics)





aluminum housing ensures the light fixture is corrosive resistant to high-risk environments. With the plastic tri-coated housing, the light fixture is protected from rapid deterioration from acid mist environments resulting in less



STAINLESS STEEL HARDWARE

Upgraded stainless steel trunnion bracket, fasteners, and quick connect specifically to withstand chemically harsh environments.

SX/EW PLANTS

LED LIGHTING SOLUTIONS



VISION X USA

1601 Boundary Blvd Auburn WA 98001 United States of America P: 253-218-2900 www.vxindustrial.com



VISION X ASIA

23-7 Dongtansandan 9-gil Dongtan-myeon Hwaseong-si Gyeonggi-do 18487, Korea P: 82-32-515-4814 www.visionxlighting.com